

NB-FST3AXLE



NUSATAMA

PT. NUSATAMA BERKAH

Jl. Raya Narogong Km. 14 Pangkalan V Bantar Gebang Bekasi 17152
Phone : 021 - 227 831 98 / 227 082 49 Whatsapp : 085211881421
e-mail : info@nusatama.com
www.nusatama.com

PT. Nusantara Berkah Tbk.
WhatsApp business account



FLATBED SEMI TRAILER TECHNICAL SPECIFICATIONS

Parameter	
Overall Length	: 13,920 mm
Overall Width	: 2,500 mm
Overall Height	: 1,510 mm
Axle Space	: 8470 + 1310 + 1310 mm
Tare Weight	: 7,980 Kg
Payload	: 31970 Kg
Fifth Wheel Height	: 1300 mm

Fabric	
Main Beam	: Q345 HTS I Beam SMAW 500
Flange and Web	: Q345 HTS Thickness 14/6/16
Side Beam	: UNP
Floor	: Checker Plate 3 mm

OEM	
Landing Gear	: FUWA 19", 28T
Kingpin Setting	: 1260 mm; Bolted type 2"
Brake System	: Dual lines air brake system, palm coupling type
Spring Leaf	: 10 leaf spring, Thickness 13 mm, Width 90 mm
Suspension	: Customized Solenoid c/w Relief Valve
Axle	: Tri-axle, 13T capacity /axle
Tire	: 12R20-18PR; 14 pcs per Chassis included spare tyre
Rim	: Steel 8.5 x 20
Toolbox	: 1 Pcs; 1 m long steel tool box
Side Guard	: Nusantara standard steel side guard bracket
Electrical System	: 24V, LED lamps

Painting	
Powder Coating	: Primer coat, top coat after sandblasting