

NB-FT16KL



NUSATAMA

PT. NUSATAMA BERKAH

Jl. Raya Narogong Km. 14 Pangkalan V Bantar Gebang Bekasi 17152
Phone : 021 - 227 831 98 / 227 082 49 Whatsapp : 085211881421
e-mail : info@nusatama.com
www.nusatama.com

PT. Nusantara Berkah Tbk.
WhatsApp business account



FUEL TRUCK 16KL TECHNICAL SPECIFICATIONS

Volume	
Volume	: 16,000 Liter
Materials	
Shell and Head	: Plate SS400 t 6 mm
Baffle	: Plate SS400 t 4.5 mm
Sub Frame	: Plate SS400 t 6 mm & 5 mm
Platform	: Checkered plate t 4.5 mm
Load Guide	: Plate SS400 t 6 mm
Hand Rail	: Medium Pipe D 1 ¼" & D 1 ½"
Main Component	
Fuel Pump	: CORKEN Fuel Vane Pump, Port size 2", flow range 550 LPM (PZ10) or equivalent
Flow Meter	: LIQUID CONTROL flow meter, model M10, port size 2", flow range 550 LPM, mechanical register (M10-C1) or equivalent
Hydraulic Pump	: VICKERS p/n 25VQ-21A or Hyva Model 145620035 or equivalent
Hydraulic Motor	: VICKERS Motor M26-42A or equivalent
Manifold Block	Customized Solenoid c/w Relief Valve
Filter	CIMTEK fuel filter CENTURION VI (Filter Housing) port size 2", flow rate 340 LPM / 90 GPM or equivalent
Hose Reel	: GRACO Hose Reel XD 40 series size 1" reel only (complete hose + ball stop) or equivalent GRACO Hose Reel XD 50 series size 1.5" reel only (complete hose + ball stop) or equivalent
Fuel Nozzle	: FLOMAX fuel nozzle complete with swivel or equivalent
Equipment	
Rear Axle	: Steel mud guard and rubber flaps
Spare Tire	: Mounted under chassis
Electric & Pneumatic Parts	
Electric Voltage	: 24 Volt
Rear Lamp Protection	: Steel Protection
Pneumatic Hose	: Nylon Tube
Finishing	
Surface Preparation	: Sand blasting and Epoxy Primer Coat thickness 90 µm
Painting	: Synthetics Paint thickness 70 µm