

NB-HBT40T



NUSATAMA

PT. NUSATAMA BERKAH

Jl. Raya Narogong Km. 14 Pangkalan V Bantar Gebang Bekasi 17152
Phone : 021 - 227 831 98 / 227 082 49 Whatsapp : 085211881421
e-mail : info@nusatama.com
www.nusatama.com

PT. Nusatama Berkah Tbk.
WhatsApp business account



HIGHBED TRAILER 40T TECHNICAL SPECIFICATIONS

Dimension (Approx.)

Overall Length	: 12,128 mm
Overall Width	: 2,550 mm
Overall Height	: 3,000 mm
Trailer Weight	: 9,380 kg
Payload	: 40,000 kg

Structure

Frame Material	: SM490YA
Top Flange	: Thickness 14 mm
Lower Flange	: Thickness 14 mm
Main Web	: Thickness 8 mm
Skid Plate	: Thickness 16 mm
Deck	: Checker Plate t 4.5 mm
Ratchet Lashing Belt	: 12,000 kg capacity
Rack Pole	: 8 pcs (Height: 1,750 mm)

Trailer

Axle	: HJ 13-ton with track length of 1,850 mm
Tire Size	: 11.00 R20
Configuration Axle	: Tri Axle T1
Suspension	: L1 suspension kit to suit 13 ton - axle
Brake & Air System	: HJ 420 x 200 30/30 Boosters
Kingpin	: JOST KZ1016 90 mm
Air Tank	: 2 x 40 Liters

Electrical System

7-core wire of 24V; 1 set of LED Hella K-LED 2.0; 10 Side Marker R/L

Accessories

JOST Modul CK1054; Rear Reflector Light; Rack Pole; Hook for lashing 12 pcs.

Painting

All surfaces to be sandblasted and cleaned/primed in red oxide/under, Side of bunks to be painted in a chip, Corrosion resistant epoxy that is non carcinogenic; Trailer to be painted white with three layers with first layer of primer coat, second and third layer of Hardtop; Sandblast should include Sandblasting Certification.