

NB-HYDMBRL



NUSATAMA

PT. NUSATAMA BERKAH

Jl. Raya Narogong Km. 14 Pangkalan V Bantar Gebang Bekasi 17152
Phone : 021 - 227 831 98 / 227 082 49 Whatsapp : 085211881421
e-mail : info@nusatama.com
www.nusatama.com

PT. Nusatama Berkah Tbk.
WhatsApp business account



HYDRAULIC UMBRELLA TECHNICAL SPECIFICATIONS

Structure

Main Column	: Steel Pipe
Base Plate	: Steel plate SS400
Anchor Bolt	: A325
Extension Column	: Steel Pipe
Support Arm	: Steel Square / Pipe
Main Arm	: Steel Profile Forming
Branch Arm	: Square Tube / Pipe
Hinge	: Pin S45C; Bushing Bronze

Hydraulic & Control System

Hydraulic System	: Vacuum Type manhole 20"
Control System	: Jurop PN45D

Canopy Fabric

Coating Material	: PVC (Polyvinyl Chloride)
Base Fabric	: High Tenacity Polyester
Total Weight	: 750 gr/m ²
Thickness	: 0.65 mm
Tensile (Warp/Weft)	: 300/300 daN/5cm
Tear (Warp/Weft)	: 30/30 daN
Resistance (Cold-Heat)	: -30- + 70°C
Flame Retardancy	: Yes
Adhesion	: 10/10 daN/5cm
Lacquering (Top/Bottom)	: PVDF / Acrylic

Accessories

Lighting	: 4 spotlight
Cover	: Zinalume or Aluminium plate
Ornaments	: Subject to customer requisition
Drainage	: PVC Pipe
Wind Sensor	: Anemometer