

NB-LBT40T



NUSATAMA

PT. NUSATAMA BERKAH

Jl. Raya Narogong Km. 14 Pangkalan V Bantar Gebang Bekasi 17152
Phone : 021 - 227 831 98 / 227 082 49 Whatsapp : 085211881421
e-mail : info@nusatama.com
www.nusatama.com

PT. Nusantara Berkah Tbk.
WhatsApp business account



LOWBED TRAILER 40T TECHNICAL SPECIFICATIONS

Dimension (Approx.)	
Overall Length	: 15.86 m
Overall Width	: 2.4 m
Overall Height	: 3.08 m
Trailer Weight	: 18,151 kg
Payload	: 55,000 kg

Structure	
Chassis	: Arc welded steel construction with sufficient tensile strength
Main floor	: 50 mm wood for main floor bolted to crossmember
Top flange	: Thickness 25 mm
Middle flange	: Thickness 10 mm
Bottom flange	: Thickness 25 mm

Trailer	
Axle	: Axle York / HJ Bridge; 3 sets
Tire	: Radial Tube Tyre 1000 x 20; 18PR; Off road, include spare tire; 13 pcs
Rim	: 7.5" x 20" include spare tire
Suspension	: York / HJ HD underslung suspension
Chassis	: Arc welded steel construction with sufficient tensile strength
Main floor	: 50 mm wood for main floor bolted to crossmember
Top flange	: Thickness 25 mm
Middle flange	: Thickness 10 mm
Bottom flange	: Thickness 25 mm
Landing Gear	: HJ Brand, lifting capacity 28,000 kg; 80,000 kg static load
Kingpin	: JOST 3.5" SAE Standard Bolted
Brake system	: York / HJ Bridge Double Chamber T30/30 (2 set) York / HJ Bridge Single Chamber T30 (4 sets)

Electrical System

24V with 7 core wire; 1 set LED combi for tail and brake light; 1 set LED side marker; 1 set LED for license plate

Ramps

2 only approx 900 mm wide ramps; Rear mounted; Hinged with grease able roller bearings; Design for easy manual operation.

Accessories

4pcs loading ramp (manual operation); 4pcs safety chain.

Painting

Chassis is completely shot blasted to SA 2.5 grade; Painted with the first layer of zinc epoxy primer, second layer of high-build polyurethane, third and fourth layers of alkyd finish top coat.