

## NB-LBT50T



**NUSATAMA**

**PT. NUSATAMA BERKAH**

Jl. Raya Narogong Km. 14 Pangkalan V Bantar Gebang Bekasi 17152  
Phone : 021 - 227 831 98 / 227 082 49 Whatsapp : 085211881421  
e-mail : [info@nusatama.com](mailto:info@nusatama.com)  
[www.nusatama.com](http://www.nusatama.com)

PT. Nusantara Berkah Tbk.  
WhatsApp business account



**LOWBED TRAILER 50T TECHNICAL SPECIFICATIONS**

Dimension (Approx.)	
Overall Length	: 15.86 m (including ramp)
Overall Width	: 2.49 m (including ramp)
Overall Height	: 3.08 m (including ramp)
Trailer Weight	: 18,151 kg
Payload	: 55,000 kg

Structure	
Chassis	: Arc welded steel construction with sufficient tensile strength
Main floor	: 50 mm wood for main floor bolted to crossmember
Top flange	: Thickness 25 mm
Middle flange	: Thickness 10 mm
Bottom flange	: Thickness 25 mm

Trailer	
Axle	: Axle York / HJ Bridge; 3 sets
Tire	: Radial Tube Tyre 1000 x 20; 18PR; Off road, include spare tire; 13 pcs
Rim	: 7.5" x 20" include spare tire; 13 pcs
Suspension	: York / HJ HD underslung suspension
Chassis	: Arc welded steel construction with sufficient tensile strength
Main floor	: 50 mm wood for main floor bolted to crossmember
Top flange	: Thickness 25 mm
Middle flange	: Thickness 10 mm
Bottom flange	: Thickness 25 mm
Landing Gear	: HJ Brand, lifting capacity 28,000 kg; 80,000 kg static load
Kingpin	: JOST 3.5" SAE Standard Bolted
Brake system	: York / HJ Bridge Double Chamber T30/30 (2 sets) York / HJ Bridge Single Chamber T30 (4 sets)

**Electrical System**

24V with 7 core wire; 1 set LED combi for tail and brake light; 1 set LED side marker; 1 set LED for license plate

**Ramps**

2 only approx. 900 mm wide ramps; Rear mounted; Hinged with grease able roller bearings; Design for easy manual operation.

**Accessories**

4pcs loading ramp (manual operation); 4pcs safety chain.

**Painting**

Steel parts are shot blasted then zinc phosphate primer, finished with acrylic type top coat paint.