

NB-LT6+1MDL



NUSATAMA

PT. NUSATAMA BERKAH

Jl. Raya Narogong Km. 14 Pangkalan V Bantar Gebang Bekasi 17152
Phone : 021 - 227 831 98 / 227 082 49 Whatsapp : 085211881421
e-mail : info@nusatama.com
www.nusatama.com

PT. Nusatama Berkah Tbk.
WhatsApp business account



LUBE TRUCK 6+1 MODULE TECHNICAL SPECIFICATIONS

Dimension (Approx.)	
Overall Length	: 4,800 mm
Overall Width	: 2,500 mm
Overall Height	: 3,500 mm
Module	: 6 Module (3 Oil, 1 Waste Oil, 1 Coolant, 1 Grease)

Structure	
Tank	: Plate SS400 t 6 mm
Baffle Thickness	: Plate SS400 t 4.5 mm
Sub Frame Thickness	: UNP150 mm , UNP100 mm
Platform Thickness	: Checkered Plate t 4.5 mm
Stiffener	: Plate SS400 t 6 mm
Hand Rail	: Medium Pipe D
Rear Cabinet	: Plate 2.6 mm (UNP100)

Pumps & Hydraulic System	
Hydraulic Pump	: VICKERS p/n 25VQ-21A; Hyva Model 145620035 or equivalent
Oil Pump	: Graco Fire Ball 300 5:1
Grease Pump	: Graco Fire Ball Pump 50:1 with high pressure
Coolant Pump	: Diaphragm Pump Husky 1050, 1"
Waste Oil Pump	: Husky 1050, 1"

Filtration System	
Hose Reel + Gun	: Samoa Hose Reel & Gun 3/4", 1/2" , & 3/8"
Oil Filter	: Sonpin Oil filter MF-12
Flow Meter	: Macnaught F025-3S4

Engine & Valves	
Compressor	: Puma
Engine	: Ingersoll
Control Valve	: 2 Bang Directional control valves
Distribute Valve	: 4 Way valve

Accessories

Steel Mudguard (Mining Spec); Fabricated Wheel Chock; 2 Fire Extinguisher.

Painting

Chassis is completely shot blasted to SA 2.5 grade; Painted with the first layer of zinc epoxy primer, second layer of high-build polyurethane, third and fourth layers of alkyd finish top coat.