

NB-MVBLCRTN



NUSATAMA

PT. NUSATAMA BERKAH

Jl. Raya Narogong Km. 14 Pangkalan V Bantar Gebang Bekasi 17152
Phone : 021 - 227 831 98 / 227 082 49 Whatsapp : 085211881421
e-mail : info@nusatama.com
www.nusatama.com

PT. Nusantara Berkah Tbk.
WhatsApp business account



MOVEABLE CURTAIN TRAILER TECHNICAL SPECIFICATIONS

Dimension (Approx.)	
Overall Bed Length	: 16,000 mm
Overall Bed Width	: 3,200 mm
Overall Bed Height	: 1,630 mm
Overall Curtain Length	: 16,000 mm
Overall Curtain Width	: 3,200 mm
Overall Curtain Height	: 1,900 mm
Payload	: 64,000 kg

Structure	
Frame	: IWF600 using Q250 600 x 200 x 17 x 11
Kingpin	: JOST KZ1016, 90 mm

Axle & Suspension System	
Axle	: 16T x 3 L1 Yonglitai or Fuwa (or Equivalent), Track 2400 mm
Suspension	: Mechanical Leaf Spring (90 x 16 x 9 mm) - 10 pcs
Axle Configuration	: Tri Axle T1

Brake & Air System	
Brake System	: WABCO 2 x RE6 relay valve
Brake Chambers	: T30/30 double chamber (6 units)
Air Tank	: 45L (2 units)

Tire & Rim	
Tire Size	: 12.00 R20 Radial Tyre
Rim Size	: 20-inch Steel Rim

Electrical System	
Wiring	: 7-core wire, 24V system
Lighting	: 8 Side Marker Lights (R/L)

Accessories

JOST Modul A400; Rear Reflector Light; 1 Tyre Holder; Hook for lashing (12 pcs); Tool Box (1 set).

Pin Lock & GP Configuration

Able to carry 1 x GP40 (40 Feet Container) or 2 GP (20 Feet Container) with 8 Twist lock location

Curtain Tarp

PVC Tarp material; ANTI UV characteristic, stamped model, smart locking system, anti-wear, anti-spill, anti-water seeping; Easy to use, light weight, rolling blinds at rear, front wall curtain to withstand high wind force

Painting

All surfaces to be sandblasted and cleaned/primed in red oxide/under; Side of bunks to be painted in a chip; Corrosion resistant epoxy that is non-carcinogenic; Trailer to be painted white with three layers; First layer of primer coat, second and third layer of Hardtop; Sandblast should include Sandblasting Certification.