

NB-SDT75CBM



NUSATAMA

PT. NUSATAMA BERKAH

Jl. Raya Narogong Km. 14 Pangkalan V Bantar Gebang Bekasi 17152
Phone : 021 - 227 831 98 / 227 082 49 Whatsapp : 085211881421
e-mail : info@nusatama.com
www.nusatama.com

PT. Nusantara Berkah Tbk.
WhatsApp business account



SDT 75CBM TECHNICAL SPECIFICATIONS

Overall Size (Approx.)	
Volume	: 80 m ³
Length	: 13.000 mm
Width	: 3.300 mm
Side Wall Height	: 2.300 mm
Inner Tipper Box Size	: 11.000 x 3.100 mm

Tipping Body	
Body	: 6 mm; High strength steel
Opening Door	: 6 mm; Wear resistance plate
Upper Beam	: 8 mm; High strength steel
Front and Rear Wall	: 8 mm; High strength steel
Floor	: 8 mm; High strength steel

Trailer	
Chassis	: Heavy duty and extra durability designed beam; Opting for high tensile steel, welded by automatic submerged-arc processes; Top flange 20mm, width 200mm; Middle flange 12mm; Bottom flange 20mm, width 200mm; Main beam height 650mm.
Axle	: 4sets; 20 TBPW, wheel track about 2.500 m
Tyre	: 16 pcs; 12.00 R24 – 18PR, without spare tire
Rim	: 16 sets; 8.5-24
Leaf Spring	: 8sets; 120 width x10 pieces x20 thickness
Suspension	: 4 sets; CIMC HUAJUN reforced type
Brake Chamber	: 4 sets; Stored chamber T30/30 4 pcs, T30 4 pcs
Landing Gear	: JOST A400R, 19 inches, two sides operation
Kingpin	: JOST 90#
Fifth Wheel	: JOST JSK 39
Tool Box	: 1.500 x540 x950 mm

Hydraulic System	
Complete Cylinder	: 4 sets
Lifting Cylinder	: 200 cylinders bore, stroke 1150; double acting cylinder, 2 sets
Opening Cylinder	: 10 cylinders bore, stroke 1000; double acting cylinder, 2 sets

Painting

Chassis is completely shot blasted to SA 2.5 grade, and painted with first layer of international zinc epoxy primer (80-100 Microns), second layer of high build polyurethane undercoat, third and fourth layers of alkyd finish top coat.

Electrical System

24-volt electrical system; 7 pin electrical connector; Parking, stop, reverse, number plate and indicator lights; Rear lights conform to European standard; Rear front & side reflectors.