

**PT. Nusatama Berkah Tbk.**

Jl. Raya Narogong Km. 14 Pangkalan V Bantar Gebang Bekasi 17152

Phone : 021 - 227 831 98 / 227 082 49 Fax: 021-8250248

Whatsapp : 085211881421

e-mail: info@nusatama.com

www.nusatama.com

PT. Nusatama Berkah Tbk.

www.nusatama.com

085211881421

021-227 831 98

021-8250248

112

EMERGENCY CALL

NUSATAMA

17152

Bekasi

Jawa Barat

Indonesia

PT. Nusatama Berkah Tbk.

www.nusatama.com

085211881421

021-227 831 98

021-8250248

112

EMERGENCY CALL

NUSATAMA

17152

Bekasi

Jawa Barat

Indonesia

SPECIFICATION



Dimension (Approx)

- Capacity : 32,970 Liter
- Tank Length : 9.8 meter
- Overall Length : 36 meter (total trailer)
- Width : 2.49 meter
- Overall Height : 4.2 meter (including handrail & walkway component)
- Payload : 48,000 kg (cargo weight)
- Weight :
 - 5,800 kg (tanker net weight)
 - 8,800 kg (trailer net weight)
 - 27,300 kg (cargo weight)
 - 43,000 kg (total operating weight)
- Tank Diameter : Oval shaped, 1.7 meter (vertical diameter), 2.5 meter (horizontal diameter)

Tanker Body

- Body : 6mm; Stainless steel
- Manhole : two manhole (600 mm x 600 mm)
- Compartment & Baffles : two
- Inlet & Outlet : two bottom inlet & outlet (front & rear of tank), four 4-inch outlet valve, four 4-inch female coupler
- Coaming : 280 mm height
- Walkway : 900 mm width, 50 mm pipe water drainage
- Other : Ladder in front & rear of tanker, storage fuel hose store in cylinder storage

Trailer

- Chassis : Heavy duty and extra durability designed i-beam; opting for high tensile steel, welded by automatic submerged-arc process; Top flange; Thickness 200 mm; Middle flange 10 mm; Bottom flange 20 mm, reinforced bottom flange 16 mm doubler plate; Width 200 mm; Main beam height 650 mm.
- Axle : 4-sets; 18T BPW, wheel track about 1,820 mm
- Tire : 16 pcs; 325/95 R24
- Rim : 16 sets; 8.5-24
- Leaf Spring : 4 sets; 100 mm width x 12 pieces x 12 mm thickness
- Suspension : 4 sets; reinforced type
- Brake chamber: 4 sets; stored chamber dual 30/30 4 pcs
- Landing Gear : Jost A400R, 19-inch two side operation
- Kingpin : Jost KZ1016 Kingpin

Electrical System

24 volt electrical system; 7 pin electrical connector; parking, stop, reverse, number plate and indicator lights; rear lights conform to european standard; rear and front side reflectors

Painting

Chassis is completely sand blasted SA 2.0-2.5, primer coat epoxy primer thickness 70 micron, top coat synthetic paint thickness 70 micron

PT. Nusatama Berkah Tbk.

Jl. Raya Narogong Km. 1.4 Pangkalan V Bantar Gebang Bekasi 17152

Phone : 021 - 227 831 98 / 227 082 49

Whatsapp : 085211881421

e-mail: info@nusatama.com

www.nusatama.com