

NB-TV32CBM



NUSATAMA

PT. NUSATAMA BERKAH

Jl. Raya Narogong Km. 14 Pangkalan V Bantar Gebang Bekasi 17152
Phone : 021 - 227 831 98 / 227 082 49 Whatsapp : 085211881421
e-mail : info@nusatama.com
www.nusatama.com

PT. Nusatama Berkah Tbk.
WhatsApp business account



TIPPING VESSEL 32CBM TECHNICAL SPECIFICATIONS

Dimension (Approx.)	
Inner Body Length	: 5,800 mm
Inner Width	: 2,300 mm
Inner Height	: 1,400 mm
Overall Width	: 2,500 mm
Volume	: 17 m ³ + 15 m ³ (Hungry Board)
Hungry Board	: 5800 x 2300 x 1300 mm

Tipping Body	
Tipping Floor	: Plate SS400 t 8 mm
Side Wall	: Plate SS400 t 6 mm with side longitudinal reinforcement
Front Wall	: Plate SS400 t 6 mm with some reinforcement
Hinge Body	: Equipped with bushing bronze and 3 greasing point
Tail Lamp & Mud Guard	: Belt conveyor rubber t 8 mm, equipped with stabilizer between tipping body and sub-frame

System Hydraulic	
Hydraulic system	: Front telescopic cylinder, operating valve inside cabin
Telescopic Cylinder	: Reborn hydraulic or equivalent

Sub Frame

Using UNP 200x80 mm with several reinforcements, both in the longitudinal direction and cross beam. Installation on the truck chassis follows the truck manufacturer's recommendations, with a subframe height of approximately 200 mm.

Painting

All plates are sandblasted before painting. The paint specifications used include epoxy primer and top coating in a colour recommended by the customer.