

NB-WT20KL



NUSATAMA

PT. NUSATAMA BERKAH

Jl. Raya Narogong Km. 14 Pangkalan V Bantar Gebang Bekasi 17152
Phone : 021 - 227 831 98 / 227 082 49 Whatsapp : 085211881421
e-mail : info@nusatama.com
www.nusatama.com

PT. Nusantara Berkah Tbk.
WhatsApp business account



WATER TANK 20KL TECHNICAL SPECIFICATIONS

Dimension (Approx.)	
Overall Length	: 12,550 mm
Overall Width	: 2,900 mm
Overall Height	: 3,170 mm
Volume	: 20,000 Liter

Materials	
Shell and Head	: Plate SS400 t 6 mm
Baffle	: Plate SS400 t 4.5 mm
Sub Frame	: Plate SS400 t 6 mm & Pl 5 mm
Platform	: Checkered plate t 4.5 mm
Load Guide	: Plate SS400 t 6 mm
Hand Rail	: Medium Pipe D 1 ¼" & D 1 ½"

Main Component	
Water Pump	: Southern Cross Centrifugal Water Pump Model 100 x 65 – 250 or equivalent
Water Canon	: Magnum 600-MM40 or equivalent
Sprayer Head	: Magnum 600-1019D-MAXI Valve 3" or equivalent
Hydraulic Pump	: Hyva Model 145620035 or equivalent
Hydraulic Motor	: Vickers Motor M26-30A-1C-20 or equivalent
Manifold Block	: Customized solenoid c/w Relief Valve

Equipment	
Rear Axle	: Steel mud guard and rubber flaps
Spare Tire	: Mounted under chassis

Electric & Pneumatic Parts	
Electric Voltage	: 24 Volt
Rear Lamp Protection	: Steel Protection
Pneumatic Hose	: Nylon Tube

Finishing	
Surface Preparation	: Sand blasting and Epoxy Primer Coat thickness 90 µm
Finishing	: Synthetics Paint thickness 70 µm